



## Commercial Dishwashers

---

### Hood Type Dishwasher New H-2



**IDEAL FOR:** Medium and small hotels, coffee shops, chain-restaurants and dining halls

**Characteristics and Advantages:**

- ✧ AISI304 stainless steel
- ✧ Imported powerful stainless steel wash pump, ensure better washing effects
- ✧ Effective rotary wash and rinse arms, more reasonable washing
- ✧ Keep the hot steam in the sealed rear door, energy saving
- ✧ Mechanical automatic control system, convenient operating
- ✧ Two wash cycles, meet different washing needs

**Technical Data:**

Name/Model	H-2
Heating	Electricity
Appearance dimension(mm)	756×835×1504
Passing width(mm)	508
Max clear entry height(mm)	420
Max capacity(rack/hour)	60
Water consumption(liter)	3
Wash tank capacity(liter)	30
Booster capacity(liter)	14
Wash temperature(°C)	60~65
Rinse temperature(°C)	82~90
Wash cycle(s)	90/60
Diameter of water inlet hose(in)	3/4
Diameter of drainpipe(in)	1 <sub>1/4</sub>
Incoming water pressure(Kg/cm <sup>2</sup> )	0.3-5
Incoming water hardness(g/l)	0.034-0.103

**Optional Configuration:**

Power Requirements	380V/50HZ/3P	380V/50HZ/3P
Incoming water temperature(°C)	10—60	40—60
Tank heater(KW)	3	3
Booster heater(KW)	7×2	7
Wash pump(KW)	0.735	0.735
Rinse pump(KW)	0.23	0.23
Total connected load(KW)	18	11
Total amps required(A)	28	17
Cross section of cable(mm <sup>2</sup> )	6	4
Rated current of air circuit breaker(A)	40	25