

CTÔRIA



REFRIGERATORS

KEEP FREEZING AS YOUR NEED

CTÔRIA

CHUZHOU CHUANGLI ELECTRICAL APPLIANCES CO.,LTD.

Add: No.402 Huzhou Road, Suzhou & chuzhou Modern Industry Park,Chuzhou, Anhui, China

E-mail: sales@chuangli.com

Website: [www.ctoria.com](http://www.ctoria.com)



# About Ctoria

**2008**  
Since

Since 2008, CHUANGLI was established and has been committing to the professional commercial refrigeration equipment development nearly 15years.

**2+**  
Brands

Now Chuangli Group are running two brands Snooker Ice Machine &Ctoria Refrigerators, two production bases are located in Shanghai and Chuzhou city.

**300+**  
Employees

The company has over 300 employees.

**60000+**  
sq/m

All production is processed in a modernization workshop which covers 60,000 sq/m with high-end CNC equipment, as well as high precision test rooms.



**CHUZHOU CHUANGLI ELECTRICAL APPLIANCES CO. LTD.** is our professional production base who is specialized in developing and manufacturing high quality commercial refrigerators / freezers. Full range of products are produced in fully-equipped modern facilities located in Chuzhou Modern Industrial Park in the Anhui province in China.



We provide a wide range of products to the international market including stainless steel upright refrigerators and freezers, under counter freezers etc which are covers most of the commercial refrigeration industry needs. We strive to provide first-class products and services to meet various customers' need.Excellence and reliability are our greatest priority.





# CONTENTS

<b>UNDER-COUNTER CHILLERS</b> 7 Product Advantages	<b>04-05</b>
<b>UNDER-COUNTER CHILLERS / FREEZERS</b> Solid Doors / Glass Doors	
KUR-09 Series(Chiller) / KUF-09 Series(Freezer)	<b>06-07</b>
KUR-12 Series(Chiller) / KUF-12 Series(Freezer)	<b>08-09</b>
KUR-15 Series(Chiller) / KUF-15 Series(Freezer)	<b>10-11</b>
KUR-18 Series(Chiller) / KUF-18 Series(Freezer)	<b>12-13</b>
<b>UPRIGHT KITCHENREF RIGERATORS</b> 9 Product Advantages	<b>14-15</b>
<b>UPRIGHT KITCHEN REFRIGERATORS</b> Solid Doors / Glass Doors	<b>16-17</b>
<b>UPRIGHT KITCHEN REFRIGERATORS</b> 2 or 4 Solid doors / Glass Doors	<b>18-19</b>
<b>UPRIGHT DUAL TEMPERATURE</b> Refrigerator / Freezer Combos	<b>20-21</b>
<b>UPRIGHT KITCHEN REFRIGERATORS</b> 3 or 6 Solid Doors	<b>22-23</b>
<b>UPRIGHT KITCHEN REFRIGERATORS</b> 400 x 600mm Grill Tray	<b>24-27</b>
<b>GN CABINET SERIES</b> 740-Single Door	<b>28-29</b>
<b>GN CABINET SERIES</b> 1400-2 Doors	<b>30-31</b>
<b>OEM OPTIONS</b>	<b>32</b>
<b>OPTIONAL POINTS</b>	<b>33</b>

# UNDER-COUNTER CHILLERS



## Product Advantages



Intelligent Digital Temperature Controller, water-proof cover design



Interior SS304 Food Grade Material



Door-open Compressor Room, easy for maintenance



Internal Radiused Corners Design  
No water leaking, easy for cleaning



Imported Brand Compressor, Ensure the Stable Refrigeration Performance



Defrosting Water Self-evaporation Design, No need drainage



High Strength Bottom Feet  
Feet broken will never happen

# UNDER-COUNTER CHILLERS / FREEZERS


Solid doors / Glass doors



## Product Parameters

MODEL	KUR-09 Series(Chiller)	KUF-09 Series(Freezer)
Temperature Range (°C)	2 ~ 8 (°C)	-18 ~ -5 (°C)
Cooling Type	Ventilated	Ventilated
Defrosting Mode	Automatic	Automatic
Exterior Dimension(W x D x H)	900 x 600 / 650 / 700 / 750 / 760 800 x 800 / 850 mm	900 x 600 / 650 / 700 / 750 / 760 800 x 800 / 850 mm
Internal Dimension(W x D x H)	410 x 445 / 495 / 545 x 565 mm	410 x 445 / 495 / 545 x 565
Capacity/L	103L / 114L / 126L	103L / 114L / 126L
Power(W)	370W	570W
Doors No.	1	1
Door Handle	Optional	Optional
Shelves No.	1	1
Ambient Temperature	43 (°C)	43 (°C)
Int./Ext Finish	SUS304 / SUS201	SUS304 / SUS201
Interior light	LED (Optional)	LED (Optional)
Castors	4 Feets	4 Feets
Refrigerant	R290	R290
Voltage	220V/50 or 60Hz/IP	220V/50 or 60Hz/IP

## 2D / Unit:mm



# UNDER-COUNTER CHILLERS / FREEZERS


## Solid Doors / Glass Doors



### Product Parameters

MODEL	KUR-12 Series(Chiller)	KUF-12 Series(Freezer)
Temperature Range (°C)	2 ~ 8 (°C)	-18 ~ -5 (°C)
Cooling Type	Ventilated	Ventilated
Defrosting Mode	Automatic	Automatic
Exterior Dimension(W x D x H)	1200 x 600 / 650 / 700 / 750 / 760 800 x 800 / 850 mm	1200 x 600 / 650 / 700 / 750 / 760 800 x 800 / 850 mm
Internal Dimension(W x D x H)	710 x 445 / 495 / 565 x 565 mm	710 x 445 / 495 / 565 x 565
Capacity/L	170L / 199L / 219L	170L / 199L / 219L
Power(W)	370W	570W
Doors No.	2	2
Door Handle	Optional	Optional
Shelves No.	2	2
Ambient Temperature	43 (°C)	43 (°C)
Int./Ext Finish	SUS304 / SUS201	SUS304 / SUS201
Interior light	LED (Optional)	LED (Optional)
Castors	4 Feets	4 Feets
Refrigerant	R290	R290
Voltage	220V/50 or 60Hz/IP	220V/50 or 60Hz/IP

### 2D / Unit:mm



# UNDER-COUNTER CHILLERS / FREEZERS


## Solid doors / Glass doors



### Product Parameters

MODEL	KUR-15 Series(Chiller)	KUF-15 Series(Freezer)
Temperature Range (°C)	2 ~ 8 (°C)	-18 ~ -5 (°C)
Cooling Type	Ventilated	Ventilated
Defrosting Mode	Automatic	Automatic
Exterior Dimension(W x D x H)	1500 x 600 / 650 / 700 / 750 / 760 800 x 800 / 850 mm	1500 x 600 / 650 / 700 / 750 / 760 800 x 800 / 850 mm
Internal Dimension(W x D x H)	1010 x 445 / 495 / 565 x 565 mm	1010 x 445 / 495 / 565 x 565 mm
Capacity/L	243L / 282L / 311L	243L / 282L / 311L
Power(W)	370W	570W
Doors No.	2	2
Door Handle	Optional	Optional
Shelves No.	2	2
Ambient Temperature	43 (°C)	43 (°C)
Int./Ext Finish	SUS304 / SUS201	SUS304 / SUS201
Interior light	LED (Optional)	LED (Optional)
Castors	4 Feet	4 Feet
Refrigerant	R290	R290
Voltage	220V/50 or 60Hz/IP	220V/50 or 60Hz/IP

### 2D / Unit:mm





# UNDER-COUNTER CHILLERS / FREEZERS


## Solid doors / Glass doors



### Product Parameters

MODEL	KUR-18 Series(Chiller)	KUF-18 Series(Freezer)
Temperature Range (°C)	2 ~ 8 (°C)	-18 ~ -5 (°C)
Cooling Type	Ventilated	Ventilated
Defrosting Mode	Automatic	Automatic
Exterior Dimension(W x D x H)	1800 x 600 / 650 / 700 / 750 / 760 800 x 800 / 850 mm	1800 x 600 / 650 / 700 / 750 / 760 800 x 800 / 850 mm
Internal Dimension(W x D x H)	1310 x 445 / 495 / 565 x 565 mm	1310 x 445 / 495 / 565 x 565 mm
Capacity/L	315L / 366L / 403L	315L / 366L / 403L
Power(W)	370W	570W
Doors No.	2 or 3	2 or 3
Door Handle	Optional	Optional
Shelves No.	3	3
Ambient Temperature	43 (°C)	43 (°C)
Int./Ext Finish	SUS304 / SUS201	SUS304 / SUS201
Interior light	LED (Optional)	LED (Optional)
Castors	4 Feets	4 Feets
Refrigerant	R290	R290
Voltage	220V/50 or 60Hz/IP	220V/50 or 60Hz/IP

### 2D / Unit:mm





UPRIGHT KITCHEN  
REFRIGERATORS



Product Advantages



# UPRIGHT KITCHEN REFRIGERATORS


## Solid doors / Glass doors



### Product Parameters

MODEL	KKR-06 Series(Chiller)	KKF-06 Series(Freezer)
Temperature Range (°C)	2 ~ 8 (°C)	-18 ~ -5 (°C)
Cooling Type	Ventilated	Ventilated
Defrosting Mode	Automatic	Automatic
Exterior Dimension(W x D x H)	610 x 760 / 800 / 850 x 1960 mm	610 x 760 / 800 / 850 x 1960 mm
Internal Dimension(W x D x H)	508 x 608 / 648 / 698 x 1480 mm	508 x 608 / 648 / 698 x 1480 mm
Capacity/L	438L	438L
Power(W)	410W	630W
Doors No.	1 or 2	1 or 2
Door Handle	Optional	Optional
Shelves No.	3	3
Ambient Temperature	43 (°C)	43 (°C)
Int./Ext Finish	SUS304 / SUS201	SUS304 / SUS201
Interior light	LED (Optional)	LED (Optional)
Castors	4 castors, 2 with brake	4 castors, 2 with brake
Refrigerant	R290	R290
Voltage	220V/50 or 60Hz/1P	220V/50 or 60Hz/1P

### 2D / Unit:mm



# UPRIGHT KITCHEN REFRIGERATORS


## 2 or 4 Solid doors / Glass doors



### Product Parameters

MODEL	KKR-12 Series(Chiller)	KKF-12 Series(Freezer)
Temperature Range (°C)	2 ~ 8 (°C)	-18 ~ -5 (°C)
Cooling Type	Ventilated	Ventilated
Defrosting Mode	Automatic	Automatic
Exterior Dimension(W x D x H)	1200 x 760 / 800 / 850 x 1960 mm	1200 x 760 / 800 / 850 x 1960 mm
Internal Dimension(W x D x H)	1098 x 608 / 648 / 698 x 1480 mm	1098 x 608 / 648 / 698 x 1480 mm
Capacity/L	960L	960L
Power(W)	510W	780W
Doors No.	2 or 4	2 or 4
Door Handle	Optional	Optional
Shelves No.	6	6
Ambient Temperature	43 (°C)	43 (°C)
Int./Ext Finish	SUS304 / SUS201	SUS304 / SUS201
Interior light	LED (Optional)	LED (Optional)
Castors	4 castors, 2 with brake	4 castors, 2 with brake
Refrigerant	R290	R290
Voltage	220V/50 or 60Hz/IP	220V/50 or 60Hz/IP

### 2D / Unit:mm






UPRIGHT DUAL TEMPERATURE  
Refrigerator / Freezer Combos



Product Parameters

MODEL	KKFR-12 Series(Chiller)	KKRF-12 Series(Freezer)
Temperature Range (°C)	-18 ~ -5 °C(UP)    2 ~ 8 °C(Bottom)	2 ~ 8 °C(Left)    -18 ~ -5 °C(Right)
Cooling Type	Ventilated	Ventilated
Defrosting Mode	Automatic	Automatic
Exterior Dimension(W x D x H)	1200 x 760 / 800 / 850 x 1960 mm	1200 x 760 / 800 / 850 x 1960 mm
Internal Dimension(W x D x H)	1098 x 608 / 648 / 698 x 1480 mm	1098 x 608 / 648 / 698 x 1480 mm
Capacity/L	441L / 441L	441L / 441L
Power(W)	720W	1000W
Doors No.	4	2 or 4
Door Handle	Optional	Optional
Shelves No.	6	6
Ambient Temperature	43 (°C)	43 (°C)
Int./Ext Finish	SUS304 / SUS201	SUS304 / SUS201
Interior light	LED (Optional)	LED (Optional)
Castors	4 castors, 2 with brake	4 castors, 2 with brake
Refrigerant	R290	R290
Voltage	220V/50 or 60Hz/IP	220V/50 or 60Hz/IP

2D / Unit:mm




UPRIGHT KITCHEN REFRIGERATORS  
3 or 6 Solid Doors



Product Parameters

MODEL	KKR-18 Series(Chiller)	KKF-18 Series(Freezer)
Temperature Range (°C)	2 ~ 8 (°C)	-18 ~ -5 (°C)
Cooling Type	Ventilated	Ventilated
Defrosting Mode	Automatic	Automatic
Exterior Dimension(W x D x H)	1800 x 760 x 1960 mm	1800 x 760 x 1960 mm
Internal Dimension(W x D x H)	1698 x 608 x 1480 mm	1698 x 608 x 1480 mm
Capacity/L	1522L	1522L
Power(W)	700W	1100W
Doors No.	3 or 6	3 or 6
Door Handle	Optional	Optional
Shelves No.	9	9
Ambient Temperature	43 (°C)	43 (°C)
Int./Ext Finish	SUS304 / SUS201	SUS304 / SUS201
Interior light	LED (Optional)	LED (Optional)
Castors	6 castors, 3 with brake	6 castors, 3 with brake
Refrigerant	R290	R290
Voltage	220V/50 or 60Hz/IP	220V/50 or 60Hz/IP

2D / Unit:mm



UPRIGHT KITCHEN REFRIGERATORS


400 x 600mm Grill Tray



Product Parameters

MODEL	KPR-06 Series(Chiller)	KPF-06 Series(Freezer)
Temperature Range (°C)	2 ~ 8 (°C)	-18 ~ -5 (°C)
Cooling Type	Ventilated	Ventilated
Defrosting Mode	Automatic	Automatic
Exterior Dimension(W x D x H)	610 x 760 / 800 / 850 x 1960 mm	610 x 760 / 800 / 850 x 1960 mm
Internal Dimension(W x D x H)	508 x 608 / 648 / 698 x 1480 mm	508 x 608 / 648 / 698 x 1480 mm
Capacity/L	438L	438L
Power(W)	410W	630W
Doors No.	1 or 2	1 or 2
Door Handle	Optional	Optional
Grill tray No.	13pcs / 400 x 600mm	13pcs / 400 x 600mm
Ambient Temperature	43 (°C)	43 (°C)
Int./Ext Finish	SUS304 / SUS201	SUS304 / SUS201
Interior light	LED (Optional)	LED (Optional)
Castors	4 castors, 2 with brake	4 castors, 2 with brake
Refrigerant	R290	R290
Voltage	220V/50 or 60Hz/1P	220V/50 or 60Hz/1P

2D / Unit:mm





UPRIGHT KITCHEN REFRIGERATORS


400 x 600mm Grill Tray



Product Parameters

MODEL	KPR-12 Series(Chiller)	KPF-12 Series(Freezer)
Temperature Range (°C)	2 ~ 8 (°C)	-18 ~ -5 (°C)
Cooling Type	Ventilated	Ventilated
Defrosting Mode	Automatic	Automatic
Exterior Dimension(W x D x H)	1200 x 760 / 800 / 850 x 1960 mm	1200 x 760 / 800 / 850 x 1960 mm
Internal Dimension(W x D x H)	1098 x 608 / 648 / 698 x 1480 mm	1098 x 608 / 648 / 698 x 1480 mm
Capacity/L	960L	960L
Power(W)	510W	910W
Doors No.	2 or 4	2 or 4
Door Handle	Optional	Optional
Grill tray No.	26pcs / 400 x 600mm	26pcs / 400 x 600mm
Ambient Temperature	43 (°C)	43 (°C)
Int./Ext Finish	SUS304 / SUS201	SUS304 / SUS201
Interior light	LED (Optional)	LED (Optional)
Castors	4 castors, 2 with brake	4 castors, 2 with brake
Refrigerant	R290	R290
Voltage	220V/50 or 60Hz/IP	220V/50 or 60Hz/IP

2D / Unit:mm




GN CABINET SERIES  
740-Single Door



Product Parameters

MODEL	EKR-074 Series(Chiller)	EKF-074 Series(Freezer)
Temperature Range (°C)	-2 ~ +8 (°C)	-22 ~ -18 (°C)
Cooling Type	Ventilated	Ventilated
Defrosting Mode	Automatic	Automatic
Exterior Dimension(W x D x H)	740 x 800 / 850 x 1960 mm	740 x 800 / 850 x 1960 mm
Internal Dimension(W x D x H)	638 x 648 / 698 x 1480 mm	638 x 648 / 698 x 1480 mm
Capacity/L	551L / 594L	551L / 594L
Power(W)	410W	630W
Doors No.	1 or 2	1 or 2
Door Handle	Optional	Optional
Shelves No.	3	3
Ambient Temperature	43 (°C)	43 (°C)
Int./Ext Finish	SUS304 / SUS201	SUS304 / SUS201
Interior light	LED (Optional)	LED (Optional)
Castors	4 castors, 2 with brake	4 castors, 2 with brake
Refrigerant	R290	R290
Voltage	220V/50 or 60Hz/IP	220V/50 or 60Hz/IP

2D / Unit:mm




GN CABINET SERIES  
1400-2 Doors



Product Parameters

MODEL	EKR-140 Series(Chiller)	EKF-140 Series(Freezer)
Temperature Range (°C)	-2 ~ +8 (°C)	-22 ~ -18 (°C)
Cooling Type	Ventilated	Ventilated
Defrosting Mode	Automatic	Automatic
Exterior Dimension(W x D x H)	1400 x 800 / 850 x 1960 mm	1400 x 800 / 850 x 1960 mm
Internal Dimension(W x D x H)	1298 x 648 / 698 x 1480 mm	1298 x 648 / 698 x 1480 mm
Capacity/L	1122L / 1210L	1122L / 1210L
Power(W)	520W	790W
Doors No.	2 or 4	2 or 4
Door Handle	Optional	Optional
Shelves No.	6	6
Ambient Temperature	43 (°C)	43 (°C)
Int./Ext Finish	SUS304 / SUS201	SUS304 / SUS201
Interior light	LED (Optional)	LED (Optional)
Castors	4 castors, 2 with brake	4 castors, 2 with brake
Refrigerant	R290	R290
Voltage	220V/50 or 60Hz/IP	220V/50 or 60Hz/IP

2D / Unit:mm





OEM OPTIONS



SALAD COUNTER FRIDGE

DRAWER COUNTER FRIDGE  
option: 1 door+3drawers or 6 drawers

OPTIONAL POINTS

